

## 



#### 5KW/15KWH Home Power Storage

All WOCOR Poweray products include CDK-5-15kWh 5KW/15KWH Home Power Storage have been certified to meet regulatory, safety, and environmental standards that meet or exceed market demand. In addition, we are committed to strict quality control, customer service, and reliability that earn the trust of our customers. A home battery and backup system is a great way to provide clean, eco-friendly energy to your entire

home this holiday season and throughout the year. And with modular systems, you can add storage batteries or solar panels as needed to keep up with changing energy needs.

#### **Product Description**

If you have a power outage and it looks like the power will be off for an extended period of time, you need backup power from a battery system or battery backup unit like CDK-5-15kWh 5KW/15KWH Home Power Storage. The CDK-5-15kWh 5KW/15KWH Home Power Storage will give you an energy capacity of 15kWh and has a power rating of 15360W .The CDK-5-15kWh 5KW/15KWH Home Power Storage has high cycle times and long life. CDK-5-15kWh 5KW/15KWH Home Power Storage offer recognized green energy, no pollution in the whole production and use process.



| Product information               |  |  |  |
|-----------------------------------|--|--|--|
| Model name                        | CDK-5-15k  | Wh   |  |
| Item                              | General Parameters   | Remark   |  |
| Battery type                      | Lithium iron<br>phosphate  |  |  |
| Output wave                       | Pure sine wave   |  |  |
| Rated capacity                    | 100.0Ah  | 0.2C after standard charging 0.2 C5 standard   |  |
| Minimum<br>capacity               | 98.0Ah   | discharging  |  |
| Nominal voltage                   | 5102V  |  |  |
|                                   |  | Fistly 0.2C5 constant current charges to 58.4V,<br>then constant voltage charges until current is less<br>than 0.05C |  |
| Expected life                     | 80% of initial capacity  | Set aside:30min  |  |
|                                   |  | Discharging :0.2 C5 to 40.0V   |  |
|                                   |  | Temperature:20±5℃  |  |
|                                   |  | Cycle time 2000 times 100%DOD  |  |
| End-off<br>discharging<br>voltage | ≥32V   | 40.0V (recommendation)   |  |
| End-off charging voltage          | ≤62.4 V  | 58.4V (recommendation)   |  |
|                                   | 16S1P  |  |  |
| Casing material                   | Metal casing   |  |  |
| Standard<br>charging              | 0.2C constant current<br>charges to<br>58.4V and constant<br>voltage to<br>58.4V, charging until<br>the<br>charging<br>current≤0.05C | Charging time:about 6 hours  |  |
| Standard<br>discharging           | Continuous<br>current:0.2C   |  |  |
| Maximum<br>charging<br>current    | End-off voltage:40.0V  |  |  |
| Maximum                           | 300A   |  |  |

# 

| continuous     |  |                            |
|----------------|--|----------------------------|
| discharging    |  |                            |
| current        |  |                            |
|                | 400.4  |                            |
| Peak current   | 400A   |                            |
| Working        | Charging: 0~45℃  |                            |
| temperature    | Discharging: -10~60℃                                       | Recommendation 23±5℃       |
| range          |  |                            |
|                | Less than one year:  |                            |
| Storage        | <b>0~25</b> ℃  | Humidity range at shipping |
| temperature    | Less than three  | state $23 \pm 5^{\circ}$   |
| range          | months:-10~35°C  |                            |
| Weight         | About 140Kg  |                            |
|                | Height:240.8cm   |                            |
| Maximum        | Width:161.2cm  |                            |
| dimension      | Length:80cm  |                            |
|                |  |                            |
| Communication  | RS485/CAN  | Support multiple inverter  |
| Machine in     | Support 16 groups n  |                            |
| parallel       | parallel   |                            |
| Protection     | 1.Over charging protection 2.over discharging protection   |                            |
| function       | 3.temperature protection 4.over current protection 5.short |                            |
| Authentication | CE/FCC/ROSH/PSE/UN3.3/MSDS/Dangerous packing certificate   |                            |
| certificate    |  |                            |

### Product Feature And Application of the CDK-5-15kWh

\*Working temperature: 0°C-60°C

- \* High cycle times and long life
- \* High energy density and conversion efficiency
- \* Adopt high-performance BMS battery management system
- \* There is sufficient insulation safety protection inside the battery
- \* Recognized green energy, no pollution in the whole production and use process
- \* Specify the specification level according to the national standard or use higher sensitivity standard to ensure the quality of the battery

