



7.5KW Portable EV Charger With LCD

7.5KW Portable EV Charger With LCD combines 5m electric wire and a charging interface that accepts AC 240V±10% input voltage, achieving automatic full in short time. The LCD display can show the detailed charging status. The 7.5KW Portable EV Charger With LCD can be use with European, American and national standard.

Product Description

7.5KW Portable EV Charger With LCD (32A 16A 7KW) with 5m cable and type 1/ type 2/GB/T plug.

This 7.5KW Portable EV Charger With LCD is the latest invention and have high-quality CE/UL, GB/T,CAS certification. The 7.5KW Portable EV Charger With LCD is made of Thermoplastic material, which has been designed to prevent the product from overheating during use of safety problems and reached grade IP54, being easy to carry. The specifications of 7.5KW Portable EV Charger With LCD(16A 32A 7KW) with model 2 portable car charger can be OEM/ODM according to your needs. WOCOR® look forward to becoming your long-term EV charger partner in china.

The 7.5KW Portable EV Charger With LCD belongs to the AC charger, and the charging power is generally 7 KW. In order to prevent safety hazards due to incorrect use, please read the equipment manual carefully before use. Do not meet the charging situations. Ensure that the power supply and wiring are in a normal state before use.

1. Do not immerse the device in water
2. Do not use in an environment that exceeds the operating temperature.
3. Do not put your fingers into the car end plug when the device is connected to the power source.
4. Do not use when the equipment and the cables are found to be damaged.
5. Do not use the device for charging other than electric vehicles.
6. The precautions for use the include but are not limited to those listed above.

Product Parameters			
Electrical Specification		Working Environment	
AC input voltage	AC 110V- 220V	Protection degree	IP54
AC power frequency	50-60 Hz	Environment	-30°C ~55°C

		temperature	
Nominalpower	7KW(Three Phase)	Relative humidity	5%~95%
Output rated current	16A/32A (Three Phase)	Maximum altitude	<2000m
Charging interface type		Cooling	Natural air cooling