



### APP EV Charger Wallbox 16A/32A Outlet

This is an app EV Charger Wallbox 16A/32A outlet and suitable for house, shopping mall and car parking use. The app EV charger Wallbox 16/32A outlet is easy to install, stable in performance and has a complete protection mechanism. The LCD display of the APP EV Charger WallBox 16A/32A outlet can show the detailed charging status.

WOCOR® look forward to becoming your

long-term EV Charger WallBox 16A/32A outlet partner in china.

### Product Description

APP EV Charger Wallbox 16A/32A Outlet - Max 22KW-20feet cable with CCS2( type2)/J1772(type1) plug

This is an APP EV Charger Wallbox 16A/32A Outlet and suitable for shopping center, car parking and service station use. It is easy to install, stable in performance, and has a complete protection mechanism. The EV Charger Wallbox 16A/32A outlet's LCD display can show the detailed charging status. The charger can be used with stand.

1. Do not connect the circuit by yourself without professional guidance
2. Do not use the charger when the inside of the plug is wet
3. Do not install the charger by yourself before reading the instructions.
4. Do not use the charger for other purposes except for electric car charging

This APP EV Charger Wallbox 16A/32A Outlet is the latest invention and have high-quality CE certification. The EV Charger Wallbox 16A/32A outlet body box is made of Aluminum alloy+Acrylic, which has been designed to prevent the product from overheating during use of safety problems and indication of working status very well. The EV Charger Wallbox 16A/32A outlet is a basic wall-mount charger and suitable for shopping malls, office properties and service stations. The charger can be used with stand.

The specifications of (32A/6A 7KW 11KW 22KW) with EV Charger Wallbox 16A/32A outlet can be OEM/ODM according to your needs. EV Charger Wallbox 16A/32A outlet combines with 5m electric cable, a charging box and electric gun. There an European standard of the EV Charger Wallbox 16A/32A outlet electric guns.

### Product Parameters

Electrical Specification		Working Environment	
AC input voltage	AC240V~AC380V	Protection degree	IP54
AC power frequency	50-60 Hz	Environment temperature	-30%~55%
Nominal power	7KW 11KW 22KW	Relative humidity	5%-95% non-condensing
Output rated current		Maximum altitude	<2000m
Charging interface type		Standby power	<4W